U.S.S.N.: 09/914,256

Page 2 of 8

Amendments to the Claims

This listing of claims will replace all prior versions, and listing, of claims in the application.

Listing of Claims:

Claims 1-8. (CANCELLED)

9 (previously presented). A foot prosthesis comprising:

a first spring element extending from a toe region to a lower leg region;

a second spring element extending from a heel region to said lower leg region;

said spring elements being connected to each other at said lower leg region; and

a tension element having two ends, which is connected with its one end to a

forward region of the first spring element and connected with its other end at said heel

region of the second spring element,

wherein said tension element is structured and arranged to be able to transmit only a tension force between its one end and its other end.

10 (previously presented). A foot prosthesis comprising:

a first spring element extending from a toe region to a lower leg region;

a second spring element extending from a heel region to said lower leg region;

said spring elements being connected to each other at said lower leg region; and

a tension element having two ends, which is connected with its one end to a

forward region of the first spring element and connected with its other end at said heel

region of the second spring element,

wherein the first and second spring elements are each a leaf spring having a ground-side surface, the springs being arranged and structured to contact and rest against each other with their ground-side surfaces facing each other.

U.S.S.N.: 09/914,256

Page 3 of 8

11 (previously presented). The foot prosthesis as claimed in claim 10, wherein said tension element is firmly connected to the ground-side surface of the forward region of the first spring element and of the heel region of the second spring element.

12 (previously presented). The foot prosthesis as claimed in claim 10, wherein said tension element is fixed at the forward end of said first spring element on an upper side thereof such, said first spring element having a slit-like opening in said forward region through which said tension element is fed toward said second spring element.

13 (previously presented). The foot prosthesis as claimed in claim 9, further comprising an adapter that connects the spring elements at the lower leg region for connection to a lower leg portion.

14 (previously presented). The foot prosthesis as claimed in claim 9, wherein said tension element is a ribbon-like element.

15 (previously presented). The foot prosthesis as claimed in claim 9, wherein said tension element is firmly connected to a ground-side of each of said spring elements.

16 (previously re-presented in independent form).

A foot prosthesis comprising:

- a first spring element extending from a toe region to a lower leg region;
- a second spring element extending from a heel region to said lower leg region;
- said spring elements being connected to each other at said lower leg region; and

a tension element having two ends, which is connected with its one end to a forward region of the first spring element and connected with its other end at said heel region of the second spring element,

wherein said tension element is fixed at the forward end of said first spring element on an upper side thereof such, said first spring element having a slit-like

U.S.S.N.: 09/914,256

Page 4 of 8

opening in said forward region through which said tension element is fed toward said second spring element.

17 (previously presented). The foot prosthesis as claimed in claim 9, wherein said first and second spring elements are formed as a concave shape when viewed from the top.

18 (previously presented). The foot prosthesis as claimed in claim 9, wherein said first and second spring elements comprise a carbon fiber composite material and said tension element comprises a stretch-free material.

19 (previously presented). The foot prosthesis as claimed in claim 9, wherein the first and second spring elements are each a leaf spring having a ground-side surface, the springs being arranged and structured to rest against each other with their ground-side surfaces facing each other.

20 (previously presented). The foot prosthesis as claimed in claim 19, wherein said tension element is firmly connected to the ground-side surface of the forward region of the first spring element and of the heel region of the second spring element.

21 (previously presented). The foot prosthesis as claimed in claim 19, wherein said tension element is fixed at the forward end of said first spring element on an upper side thereof such, said first spring element having a slit-like opening in said forward region through which said tension element is fed toward said second spring element.

22 (previously presented). The foot prosthesis as claimed in claim 9, wherein said tension element is fixed at the forward end of said first spring element on an upper side thereof such, said first spring element having a slit-like opening in said forward region through which said tension element is fed toward said second spring element.

U.S.S.N.: 09/914,256

Page 5 of 8

Please add the following new claims, dependent from allowed claim 16.

23 (new). The foot prosthesis as claimed in claim 16, wherein said first and second spring elements are formed as a concave shape when viewed from the top.

24 (new). The foot prosthesis as claimed in claim 16, wherein said first and second spring elements comprise a carbon fiber composite material and said tension element comprises a stretch-free material.